

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	684.2954
	First Named Inventor or Application Identifier	
	ETSURO KISHI, ET AL.	
	Express Mail Label No.	

jc564 U.S. PTO
01/07/00
09/479245

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231	
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification Total Pages 61</p> <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) Total Sheets 9</p> <p>4. <input checked="" type="checkbox"/> Oath or Declaration Total Pages 2</p> <p>a. <input checked="" type="checkbox"/> Newly executed (original or copy)</p> <p>b. <input type="checkbox"/> Unexecuted for information purposes</p> <p>c. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below]</p> <p>i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed Statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4c is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4c, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.</p>		<p>6. <input type="checkbox"/> Microfiche Computer Program (Appendix)</p> <p>7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)</p> <p>a. <input type="checkbox"/> Computer Readable Copy</p> <p>b. <input type="checkbox"/> Paper Copy (identical to computer copy)</p> <p>c. <input type="checkbox"/> Statement verifying identity of above copies</p>
ACCOMPANYING APPLICATION PARTS		
<p>8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s))</p> <p>9. <input type="checkbox"/> 37 CFR 3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney</p> <p>10. <input type="checkbox"/> English Translation Document (if applicable)</p> <p>11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations</p> <p>12. <input type="checkbox"/> Preliminary Amendment</p> <p>13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)</p> <p>14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application Statement(s) Status still proper and desired</p> <p>15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)</p> <p>16. <input type="checkbox"/> Other: _____</p>		

Assignment Document

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____

18. CORRESPONDENCE ADDRESS

<input checked="" type="checkbox"/> Customer Number or Bar Code Label	05514 (Insert Customer No. or Attach bar code label here)	or <input type="checkbox"/> Correspondence address below
NAME		
Address		
City	State	Zip Code
Country	Telephone	Fax

+

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	12-20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	2-3 =	0	X \$ 78.00 =	\$ 0.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$ 260.00 =	\$ 0.00
				BASIC FEE (37 CFR 1.16(a))	\$ 690.00
			Total of above Calculations =		\$ 690.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				
	TOTAL =				\$ 690.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 690.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ _____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☐ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	T. Thomas C. Gellenthien - Reg. No. 39,683
SIGNATURE	<i>T. Gellenthien</i>
DATE	January 7, 2000

TTCG\lmj

FIELD OF THE INVENTION AND RELATED ART

In recent years, accompanying the progress of data processing apparatus, there has been an increasing demand for a display device requiring a small power consumption and a small thickness, and extensive study and development have been made on devices satisfying such a demand. Among these, a liquid crystal display device wherein an alignment of liquid crystal molecules is electrically controlled to change optical characteristics has been extensively developed and commercialized as a display device satisfying the demand described above.

Reflection-type display devices are expected

from the viewpoints of lower power consumption and less visual load on human eyes. As a type thereof, there has been proposed an electrophoretic display device wherein colored charged particles are moved in an insulating liquid (e.g., in U.S. Patent No. 3,668,106). Figure 7 is a sectional view of a most typical example of such electrophoretic display device.

Referring to Figure 7, an electrophoretic display device includes an electrophoretic layer EL comprising a colored insulating liquid 6 and colored charged particles 7 dispersed thereon, and a pair of or pairs of opposing electrodes 4 and 5 disposed to sandwich the electrophoretic layer EL, wherein the electrophoretic layer EL is supplied with a voltage via the opposing electrodes to cause the colored charged particles 7 to migrate toward and be fixed at an electrode biased to a polarity opposite to that of the colored charged particles 7 to effect a display by utilizing a difference between the color of colored charged particles 7 and a dyed color of the insulating liquid 6. More specifically, when the particles 7 are attached to the surface of the electrode 4 closer to the viewer, the color of the particles 7 is displayed, and when the particles 7 are attached to the electrode 5 remoter from the viewer, the color of the dyed insulating layer 6 is displayed.

5

10

20

25

shown in Figure 8B, a slight leakage of charge retained at the electrode gradually proceeds through the electrophoretic layer EL . Accordingly, even if the electrophoretic layer is set to have a high specific resistance on the order of 10^{15} ohm.cm. the available memory time is at most ten and several hours to several tens hours and cannot be said to be sufficient.

10 SUMMARY OF THE INVENTION

In view of the above-mentioned problems, an object of the present invention is to provide an electrophoretic display device capable of realizing a stable memory characteristic for a long period without relying on a charge retained at electrodes or requiring a switching control between open and closed states.

According to the present invention, there is provided an electrophoretic display device of a cell structure, comprising: at least two electrodes. fixing surfaces each associated with one of said at least two electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing migration of the colored charged particles toward

and collective attachment onto one of the fixing surfaces; wherein at least one of the fixing surfaces and the colored charged particles is provided with an adhesive layer allowing repetitive attachment thereto and separation therefrom of the colored charged particles.

According to another aspect of the present invention, there is provided an electrophoretic display device of a cell structure, comprising: at least two electrodes, fixing surfaces each associated with one of said at least two electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing migration of the colored charged particles toward and collective attachment onto one of the fixing surfaces; wherein the fixing surfaces are provided with a charged film having a constant surface charge of a polarity opposite to that of the colored charged particles.

These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following description of the preferred embodiments of the present invention taken in conjunction with the

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 2 is a schematic sectional view of another embodiment of the electrophoretic display device according to the invention.

Figures 4 - 6 respectively show another
15 embodiment of the electrophoretic display device
according to the invention.

Figures 8A - 8C are schematic sectional views for illustrating an operation principle of the conventional electrophoretic display device.

Figures 11A - 11C are schematic sectional views for illustrating an operation principle of an

embodiment of the electrophoretic display device according to the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 (First Embodiment)

An electrophoretic display device according to this embodiment of the present invention is characterized by having a cell structure including: at least two electrodes, fixing surfaces each associated with one of the two electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing migration of the colored charged particles toward and collective attachment onto one of the fixing surfaces; wherein at least one of the fixing surfaces and the colored charged particles is provided with an adhesive layer allowing repetitive attachment thereto and separation therefrom of the colored charged particles.

The adhesive layer as a characteristic of this embodiment may be disposed on only the fixing surfaces, on only the surface of the colored charged particles, or on both of the fixing surfaces and the surface of the colored charged particles. In case where the adhesive layers is disposed on only one of

the fixing surfaces and the colored charged particles, the other may preferably be composed of a material selected so as to impart optimum adhesiveness and peelability to the adhesive layer in consideration of the fact that adhesiveness and peelability are largely affected by the surface energy and solubility parameter of the other side material.

The adhesive layer is required to allow repetitive attachment thereto and separation therefrom of the colored charged particles, to be insoluble in the insulating liquid and, in case where it is formed on the surface of the colored charged particles, not to impair the dispersibility of the colored charged particles in the insulating layer.

For comply with these requirements, the adhesive layer may suitably comprise a polymer having a glass transition temperature (T_g) of -35°C to $+35^{\circ}\text{C}$ and comprising at least one polymer species selected from the group consisting of poly(meth)acrylate esters, poly(meth)acrylic acid poly(meth)acrylonitrile, poly(meth)acrylamide, polyvinyl esters and polyvinyl ethers, so as to provide a tackiness at an operating temperature suitable for repetitive attachment and peeling as exhibited by "Post-it" (trade name, available from 3M Co.) extensively used as memo-slip or tag paper.

Figure 1 is a schematic sectional view of an

embodiment of the electrophoretic display device according to the present invention. An electrophoretic display device shown in Figure 1 includes two (closed) cell structures, each of which comprises a transparent (display-side) substrate 1, a counter substrate 2 and a partitioning wall 3 to form a cell, which is filled with an electrophoretic layer EL comprising a colored insulating layer 6 and colored charged particles 7 colored in a different color from the colored insulating layer 6. In each cell, the transparent display substrate 1 has thereon a transparent display electrode 4, and the counter substrate 2 has thereon a counter electrode 5. Each of the transparent display electrode 4 and the counter electrode 5 has a fixing surface 13 onto which the colored charged particles 7 are collectively attached. The fixing surface 13 is coated with an adhesive layer 8 allowing repetitive attachment thereto and separation therefrom of the colored charged particles 7.

Now, the operation principle for a unit cell of the display device will be described with reference to Figures 3A to 3C. As explained with reference to Figure 1, each cell structure of the display device includes mutually opposing two substrates 1 and 2, a transparent display electrode 4 formed on the transparent display substrate 1, a counter electrode 5

formed on the counter electrode 2, a colored insulating layer 6 disposed between the opposing electrodes 4 and 5, colored charged particles 7 dispersed in the colored insulating layer 6 (and assumed herein to be positively charged), and adhesive layers 8.

Now, if an external circuit 10 is connected as shown in Figure 3A to induce a negative charge at the transparent display electrode 4 and a positive charge at the counter electrode 5, the positively charged colored charged particles 7 are collected and attached onto the transparent display electrode 4, whereby the display surface exhibits the color of the colored charged particles 7.

Then, if the external circuit 10 is turned open as shown in Figure 3B, the charges on the respective electrodes are retained, whereby the colored charged particles 7 are fixedly attached onto the transparent display electrode 4 due to an electrostatic attractive force exerted by the retained charge.

Now, if the external circuit 10 is short-circuited as shown in Figure 3, the charges retained at the electrodes 4 and 5 are released to lose the electrostatic attraction. In this state, however, the colored charged particles 7 are retained by attachment or adsorption to the adhesive layer 8 formed on the

electrode 4, thus retaining the display state.

Accordingly, even in a drive system such as a simple matrix drive wherein the circuit-open state is not effectively retained, a good memory characteristic is exhibited. Further, as the surface charge on the adhesive layer 8 is never released, a stable memory characteristic can be realized for a long period.

On the other hand, the rewriting of a display state is performed by peeling or separating the colored charged particles 7 from the adhesive layer 8 on the electrode 4 by applying reverse-polarity voltages to the electrodes 4 and 5 by connecting the external circuit 10 as represented by a dotted line in Figure 3C, i.e., to apply a positive charge to the electrode 4 and a negative charge to the electrode 5, so as to exert an energy exceeding a drive voltage threshold corresponding to the adsorption energy of the adhesive layer 8. In this way, by optimizing the adhesive force exerted by the adhesive layer 18, it becomes possible to design threshold characteristics essential for a simple matrix drive.

The effectiveness of the present invention is not restricted to the above-described organization but can be applied to any electrophoretic display device having a fixing surface or charged particles. Examples thereof may include: a display electrode/masking electrode-type display device as

disclosed in JP-A 9-021149 and modified to include an adhesive layer on a fixing surface 14 as shown in Figure 4; a horizontal movement-type display device as disclosed in JP-A 10-005727 and modified to include an adhesive layer 8 on a fixing surface 14 as shown in Figure 6; and a microcapsule-type display device as disclosed in JP-A 1-086116 including polymer capsules 12 containing an insulating layer 6 and modified to use adhesive colored charged particles 13 exhibiting a surface-adhesive colored charged particles 13 exhibiting a surface adhesiveness as shown in Figure 6. Each cell can include 3 or more electrodes so as to provide at least one third electrode for controlling the movement of electrophoretic particles in addition to two drive electrodes as disclosed in U.S. Patent No. 4,203,106 with further modification to provide one of the drive electrodes or the electrophoretic particle surface.

The organization of the adhesive layer will now be described in further detail.

Preferred examples of the material for the adhesive layer may include: poly(meth)acrylate esters, i.e., polymers of acrylic acid esters and methacrylic acid esters. Specific examples thereof may include: polyalkyl (meth)acrylates; such as polymethyl (meth)acrylate, polyethyl (meth)acrylate, polypropyl (meth)acrylate, poly-n-butyl(meth)acrylate,

5

10

20

25

containing esters, such as 2,2,3,3-tetrafluoropropyl
acrylate; esters having a polar group, such as 2-
hydroxypropyl acrylate; and other polar monomers, such
as (meth)acrylic acid, (meth)acrylonitrile,
5 methacrylamide, vinyl acetate and other esters. It is
also possible to control the adhesiveness and
peelability of these polymers by regulating molecular
weight, orientation or crystallinity, and presence or
absence of crosslinkage. In addition to
10 copolymerization, it is possible to mix or laminate
such adhesive polymers.

In addition to the above-mentioned acrylate-
based resins, it is also possible to use polymers
predominantly comprising polymerized units of
15 (meth)acrylic acid, (meth)acrylonitrile,
(meth)acrylamide, vinyl esters and vinyl ethers.

Specific examples of (co)monomers providing
such adhesive (co)polymers may include: styrene, o-
methylstyrene, m-methylstyrene, p-methoxystyrene, p-
20 ethylstyrene, p-t-butylstyrene, acrylic acid, methyl
acrylate, ethyl acrylate, n-butyl acrylate, n-propyl
acrylate, isobutyl acrylate, octyl acrylate, dodecyl
acrylate, 2-ethylhexyl acrylate, stearyl acrylate, 2-
chloroethyl acrylate, phenyl acrylate, methacrylic
25 acid, methyl methacrylate, ethyl methacrylate, n-
propyl methacrylate, n-butyl methacrylate, isobutyl
methacrylate, n-octyl methacrylate, dodecyl

methacrylate, 2-ethylhexyl methacrylate, stearyl
methacrylate, phenyl methacrylate, dimethylaminomethyl
methacrylate, diethylaminoethyl methacrylate, 2-
hydroxyethyl methacrylate, acrylonitrile,
5 methacrylonitrile, acrylamide, methyl vinyl ether,
ethyl vinyl ether, propyl vinyl ether, n-butyl vinyl
ether, isobutyl vinyl ether, β -chloroethyl vinyl
ether, phenyl vinyl ether, p-methylphenyl vinyl ether,
p-chlorophenyl vinyl ether, p-bromophenyl vinyl ether,
10 p-nitrophenyl vinyl ether, p-methoxyphenyl vinyl
ether, 2-vinylpyridine, 3-vinylpyridine, N-
vinylpyrrolidone, 2-vinylimidazole, N-methyl-2-
vinylimidazole, N-vinylimidazole, butadiene, fumaric
acid, maleic acid, itaconic acid, and salts of these.

15 These polymers may be obtained by
polymerization using various initiators, examples of
which may include: azo or diazo-type polymerization
initiators, such as 2,2'-azobis(2,4-dimethyl-
valeronitrile), 2,2'-azobisisobutyronitrile, 1,1'-
20 azobis(cyclohexane-1-carbonitrile) and 2,2'-azobis-4-
methoxy-2,4-dimethylvaleronitrile; and peroxide-type
polymerization initiators, such as benzoyl peroxide,
methyl ethyl ketone peroxide, diisopropyl
peroxycarbonate, cumene hydroperoxide, 2,4-
25 dichlorobenzoyl peroxide and lauroyl peroxide.

Adhesiveness or tackiness between two
substances may be evaluated based on solubility

004040-54264750

parameters (SP values) of the two substances. Two substrates having closer SP values may exhibit a better mutual solubility, and in case where one is solid, exhibit a better wettability (e.g., as disclosed in "Adhesive Handbook" published from Nikkan Kogyo Shimbun K.K.). Polymers may exhibit an SP values over a broad range of from 6 of polytetrafluoroethylene to 16 of polyacrylonitrile. Accordingly, in the present invention, it is preferred to select an adhesive layer material in view of the SP value of the materials constituting the fixing surface or the colored charged particles.

The adhesive colored charged particles (e.g., 13 as shown in Figure 2 or Figure 6) used in the present invention can be formed by surface-coating colored charged particles with an adhesive layer but may suitably be composed of a colored adhesive material. More specifically, such adhesive colored particles may preferably be formed through suspension polymerization or emulsion polymerization while they can also be formed through bulk polymerization or solution polymerization.

The adhesion or adsorption force of such adhesive colored particles onto the fixing surface can be controlled to some extent by adjustment of average particle size. Particles having an average particle size of ca. 5 μ m are liable to exhibit too strong an

adhesive force onto the fixing surface and thus a lower peelability. On the other hand, particles having an average particle size exceeding ca. 70 μm have a smaller contact area with the fixing surface, thus posing a difficulty in ensuring an appropriate level of adhesion force. Accordingly, it is preferred to provide an average particle size in a range of ca. 5 - 70 μm .

In order to prevent agglomeration and ensure a dispersion state of colored particles during suspension or emulsion polymerization and in a colored insulating layer within the display device, it is preferred to add an appropriate dispersant.

Examples of such dispersant may include:

polyvalent metal salts of phosphoric acid, such as calcium phosphate, aluminum phosphate and zinc phosphate; carbonic acid salts, such as calcium carbonate, and magnesium carbonate; other inorganic salts, such as calcium metal silicate, calcium sulfate, and barium sulfate; inorganic (hydro)oxides, such as calcium hydroxide, magnesium hydroxide, aluminum hydroxide, silica, bentonite and alumina; surfactants, such as sodium dodecylbenzenesulfonate, sodium tetradecyl sulfate, sodium pentadecyl sulfate, sodium octyl sulfate, sodium oleate, sodium laurate, sodium stearate, and potassium stearate; and polymeric dispersants, such as polyvinylpyrrolidone and

polyvinyl alcohol having various saponification degree and molecular weights.

Examples of colorants for coloring the charged particles may include: titanium oxide,

- 5 carbon black, nigrosine, iron black, Aniline Blue, Chalcoil Blue, Chrome Yellow, Ultramarine Blue, Dupont Oil Red, Quinoline Yellow, Methylene Blue Chloride, Phthalocyanine Blue, Malachite Green Oxalate, Lamp Black, Rose Bengal, C.I. Pigment Red, C.I. Pigment
- 10 Yellow, C.I. Pigment Blue, C.I. Direct Red 1, C.I. Direct Red 4, C.I. Acid Red 1, C.I. Basic Red 1, C.I. Mordant Red 30, C.I. Direct Blue 1, C.I. Direct Blue 2, C.I. Acid Blue 9, C.I. Acid Blue 15, C.I. Basic Blue 3, C.I. Basic Blue 5, C.I. Mordant Blue 7, C.I.
- 15 Direct Green 6, C.I. Basic Green 4, C.I. Basic Green 6, Lead Yellow, Cadmium Yellow, Mineral Fast Yellow, Navre Yellow, Naphthol Yellow S, Hansa Yellow G, Permanent Yellow NCG, Turtradine Lake, Molybdenum Orange, Permanent Orange G, Cadmium Red, Permanent
- 20 Red 4R, Watching Red Calcium salt, Brilliant Carmine 3B, Fast Violet B, Methyl Violet Lake, Ultramarine, Cobalt Blue, Alkali Blue Lake, Victoria Blue Lake, Quinacridone, Rhodamine B, Fast Sky Blue, Pigment Green B, Malachite Green Lake, and Final Yellow
- 25 Green G.

It is also possible to use a magnetic colorant, examples of which may include: Be-ferrites,

000000-000000

Sr-ferrite, Pb-ferrites, magnetite, gamma-Fe₂O₃ and acircular magnetic materials, such as Co-ferrites. These may be used alone or in mixture thereof or in mixture with soft ferrite particles.

5 The (adhesive) colored charged particles used
in the present invention can optionally contain a
charge control agent, inclusive of negative charge
control agents, such as metal complex salts of monoazo
dyes, and metal complex salts of salicylic acid, alkyl
10 salicylic acids, dialkylsalicylic acids and naphthoic
acid; and positive charge control agents, such as
nigrosine compounds, and organic quaternary ammonium
salts.

(Second Embodiment)

15 An electrophoretic display device according to this embodiment of the present invention is characterized by a cell structure, including: at least two electrodes, fixing surfaces each associated with one of the two electrodes, an electrophoretic layer
20 disposed in the cell and comprising an insulating liquid and colored charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing migration of the colored charged particles
25 toward and collective attachment onto one of the fixing surfaces; the fixing surfaces are provided with a charged film having a constant surface charge of a

polarity opposite to that of the colored charged particles.

The charged film may comprise a ferroelectric film or an electret film.

5 It is preferred that the insulating layer contains a polar ion-adsorbing agent, such as alumina or silica, so as to suppress the ion concentration in the insulating layer, thereby providing a high insulating property as represented by a volumetric resistivity of at least 10^{12} ohm.cm, preferably at 10 least $10^{12} - 10^{15}$ ohm.cm. As a result, the decrease in surface charge of the charged film due to ion adsorption becomes negligible.

Figure 9 is a schematic sectional view of an embodiment of the electrophoretic display device according to the present invention. An electrophoretic display device shown in Figure 9 includes two (closed) cell structures, each of which comprises a transparent (display-side) substrate 1, a counter substrate 2 and a partitioning wall 3 to form a cell, which is filled with an electrophoretic layer EL comprising a colored insulating layer 6 and colored charged particles 7 colored in a different color from the colored insulating layer 6. In each cell, the transparent display substrate 1 has thereon a transparent display electrode 4, and the counter substrate 2 has thereon a counter electrode 5. Each

of the transparent display electrode 4 and the counter electrode 5 has a fixing surface 13 onto which the colored charged particles 7 are collectively attached. The fixing surface 13 is coated with a charged film 18 having a constant charge of a polarity (negative in the embodiment of Figure 9) opposite to that of the colored charged particles 7.

Now, the operation principle for a unit cell of the display device will be described with reference to Figures 11A to 11C. As explained with reference to Figure 9, each cell structure of the display device includes mutually opposing two substrates 1 and 2, a transparent display electrode 4 formed on the transparent display substrate 1, a counter electrode 5 formed on the counter electrode 2, a colored insulating layer 6 disposed between the opposing electrodes 4 and 5, colored charged particles 7 dispersed in the colored insulating layer 6 (and assumed herein to be positively charged), and charged films 18.

Now, if an external circuit 10 is connected as shown in Figure 11A to induce a negative charge at the transparent display electrode 4 and a positive charge at the counter electrode 5, the positively charged colored charged particles 7 are collected and attached onto the transparent display electrode 4, whereby the display surface exhibits the color of the

colored charged particles 7.

Then, if the external circuit is turned open as shown in Figure 11B, the charges on the respective electrodes are retained, whereby the colored charged particles 7 are fixedly attached onto the transparent display electrode 4 due to an electrostatic attractive force exerted by the retained charge.

Now, if the external circuit 10 is short-circuited as shown in Figure 11C, the charges retained at the electrodes 4 and 5 are released to lose the electrostatic attraction. In this state, however, the colored charged particles 7 are retained by an electrostatic force exerted by the negative charge held by the charged film 18 formed on the electrode 4, thus retaining the display state.

Accordingly, even in a drive system such as a simple matrix drive wherein the circuit-open state is not effectively retained, a good memory characteristic is exhibited. Further, as the surface charge on the charged film 18 is never released, a stable memory characteristic can be realized for a long period.

On the other hand, the rewriting of a display state is performed by peeling or separating the colored charged particles 7 from the charged film 18 on the electrode 4 by applying reverse-polarity voltages to the electrodes 4 and 5 by connecting the external circuit 10 as represented by a dotted line in

Figure 11C, i.e., to apply a positive charge to the electrode 4 and a negative charge to the electrode 5, so as to exert an energy exceeding a drive voltage threshold corresponding to the electrostatic force given by the charged film 18. In this way, by optimizing the electrostatic force exerted by the charged film 18, it becomes possible to design threshold characteristics essential for a simple matrix drive.

The effectiveness of the present invention is not restricted to the above-described organization but can be applied to any electrophoretic display device having a fixing surface or charged particles. Examples thereof may include: a display electrode/masking electrode-type display device as disclosed in JP-A 9-021149 and modified to include a charged film 18 on a fixing surface 14 as shown in Figure 12; a horizontal movement-type display device as disclosed in JP-A 10-005727 and modified to include a charge film 18 on a fixing surface 14 as shown in Figure 13; and a microcapsule-type display device as disclosed in JP-A 1-086116 including polymer capsules 12a forming a fixing surface 14, containing an insulating layer 6 and colored charged particles 7 therein and also modified to be formed of charged films 18a as shown in Figure 14, wherein the fixing surface 14 is given by an external surface of a

microcapsule 12.

The charged film 18 may preferably comprise a ferroelectric material or an electret material.

Examples of the ferroelectric material suitably used in the present invention may include: inorganic compound, such as lead zirconate titanate (PZT), lanthanum-added lead zirconate titanate (PLZT), and barium titanate; and organic polymers, such as polyvinylidene fluoride (PVDF) and vinylidene fluoride-trifluoroethylene (VDF/TrFE) copolymer. By forming a charged film of such a ferroelectric material, it is possible to form a very large surface charge as large as 100 - 20000 nC/cm².

The electret-forming materials used in the present invention may include dielectric materials in general, inclusive of inorganic materials, such as glass, but may preferably comprise organic polymer materials capable of utilizing a printing process for the film formation in view of productivity. It is preferred to use fluorine-containing resins, such as polytetrafluoroethylene, tetrafluoroethylene-trifluoroethylene copolymer, polytetrafluoroethylene, FEP copolymer (tetrafluoroethylene-hexafluoropropylene copolymer), in view of performances, and it is also possible to suitably use other polymers, such as polyethylene, polypropylene, polystyrene, polymethyl methacrylate, polyvinyl chloride, polyethylene

terephthalate, and polyimide. An electret film may desirably have a surface charge (density) of at least 5 nC/cm² and possibly ca. 50 nC/cm² at the maximum.

The significance of electret material is supplemented below. "Electret" has been named after "magnet" based on their similarity and is a material persistently retaining induced polarization to provide an external electric field thereof.

An electret is formed through polarization and retainment (or freezing) thereof. In this embodiment, the retainable or persistent polarization is representatively set up by (i) charge separation caused by microscopic or macroscopic displacement of ions contained in a paraelectric material, (ii) anisotropic alignment of intra-molecular dipole composed of a polar group, etc., by an external electric field, or (iii) charge injection by corona discharge caused by a corona discharge electrode or occurring at gaps between an electrode and a dielectric.

Ion charge separation or a polarized charge by dipole alignment provides a hetero-charge of a polarity different from that of an external field application electrode, and a spatial charge caused by charge injection from an external electrode as by corona discharge provides a homo-charge of a polarity identical to that of the external electrode.

According to measurement by a thermal stimulation current (TSC), the freezing or retainment of a polarization charge is considered to be caused by a deep trap, etc. of electrons, holes or ions present at non-aligned regions, such as crystal grain boundaries, within a paraelectric body, particularly a region close to the surface thereof.

Electret formation may be performed through various processes, inclusive of, e.g., the following processes:

- (1) A paraelectric material heated to a proximity of softening temperature or melting temperature is cooled under application of a high DC electric field (thermo-electret process).
- (2) Corona discharge onto a paraelectric material surface or a high DC electric field (up to ca. 10^6 V/cm) close to a breakdown voltage is applied across a paraelectric material at room temperature (electro-electret process).
- (3) Irradiation of a paraelectric material with high-energy radiation (such as electron rays and gamma-rays) in vacuum (radio-electret process).
- (4) Application of a high DC voltage onto a paraelectric material under photo-illumination (photo-electret process).
- (5) Mechanical deformation as by pressurization, stretching, etc. (mechano-electret process).

0040945-01000

Hereinbelow, some specific examples of the electrophoretic display device according to the present invention will be described.

Example 1

5 Figure 1 shows an example of electrophoretic display device including two closed cells each corresponding to a display segment (or pixel) and comprising two opposing electrodes 4 and 5 each having thereon an adhesive layer 8. More specifically, each
10 cell is defined by a display-side transparent substrate 1, a counter substrate 2 and a partitioning wall 3, and is filled with an electrophoretic layer (EL)-forming mixture comprising a colored insulating liquid 6 and colored charged particles 7 dispersed in
15 the insulating liquid 6. In each cell, the display-side transparent substrate 1 is provided with a transparent display electrode 4 and the counter substrate 2 is provided with a counter electrode 5. Each of the display electrode 4 and the counter
20 electrode 5 is coated with an adhesive layer 8.

The electrophoretic display device may be produced along a process described hereinbelow.

Transparent display electrode 4 are formed on a transparent display substrate 1, and counter
25 electrodes 5 are formed on a counter substrate 2. Each of the substrates 1 and 2 may be formed of a material showing a high transmittance for visible

000000-5456460

light and a high heat resistance, examples of which may include: inorganic materials, such as glass and quartz; and polymer films, such as polyethylene terephthalate (PET) and polyether sulfone (PES). In 5 this example, glass substrates were used.

The transparent display electrode 4 may be formed of any transparent conductor material capable of patterning. In this example, a 200 nm-thick indium tin oxide (ITO) film was formed by vapor deposition 10 and patterned into electrodes 4. The counter electrodes 5 may also be formed of such transparent conductor materials and also of metal conductor materials. In this example, a 200 nm-thick Al film was formed by vapor deposition and patterned into 15 electrodes 5.

The adhesive layer 8 was formed of a n-butyl acrylate-n-butyl methacrylate copolymer. More specifically, 50 wt. parts of n-butyl acrylate and 50 wt. parts of n-butyl methacrylate were dissolved in 20 toluene to form a 10 wt. % solution, and 1 wt. % of 2,2'-azobisisobutyronitrile was added thereto as a polymerization initiator, followed by 3 hours of polymerization under heating at 70 °C, to form a polymer solution.

25 The substrates 1 and 2 carrying the patterned electrodes 4 and 5, respectively, were coated with a resist so as to selectively expose the electrodes 4

and 5, and then coated with the polymer solution by spin coating, followed by evaporation of the solvent and removal of the resist to leave a ca. 500 nm-thick transparent adhesive layer 8 on each of the electrodes 4 and 5. The resultant polymer exhibited a glass transition (T_g) of -15.4°C as measured by using a differential scanning calorimeter ("DSC3100", mfd. by Mac Science K.K.).

Then, partitioning walls 3 are formed on the counter substrate 2. The partitioning walls 3 may suitably be formed of a polymer material through any processes, e.g., a process including a sequence of application of a photosensitive resin layer, exposure and wet development; a process of bonding separately produced partitioning walls; or a process of forming partitioning walls by molding on a light transmissive counter substrate 2. In this example, a process including application of photosensitive varnish, exposure and wet development was repeated in three cycles to form 50 μm -high partitioning walls 3.

Then, an electrophoretic layer-forming mixture comprising a colored insulating liquid 6 and colored charged particles 7 is placed within the partitioning walls. The colored insulating liquid 6 may be formed by dispersing or dissolving a colorant, such as dye, in an insulating liquid, such as silicone oil, toluene, xylene or high-purity kerosene.

In this example, the colored insulating liquid 6 was formed by dispersing an anthraquinone-based black dye in silicone oil.

The colored charged particles 7 may comprise pigment particles or resin particles of e.g., polyethylene or polystyrene containing powdery pigment dispersed therein capable of being charged in the colored insulating liquid 6. The colored charged particles 7 may generally have an average particle size on the order of 0.1 - 50 μm . In this example, white particles having an average particle size of 0.5 μm and prepared by dispersing white powdery pigment (titanium oxide) in polyethylene particles. The white resinous particles 7 thus prepared were confirmed to be positively charged in the above-prepared colored insulating liquid 6.

Finally, the transparent substrate 1 was applied onto the partitioning walls 3 with a bonding agent to form a display device having a structure as shown in Figure 1 including two closed cells each measuring ca. 500 μm x ca. 500 μm .

Comparative Example 1

A display device was prepared in the same manner as in Example 1 except for omitting the adhesive layers 8.

(Operation)

The thus-prepared two display devices having

similar structures as shown in Figure 1 except for the presence or absence of the adhesive layers 8 were driven by a drive circuit (not shown). More specifically, first, the electrodes 4 of a left cell and a right cell of each device were supplied with -50 volts and +50 volts, respectively, relative to the counter electrodes 5. As a result, in the left cell, the positively charged white particles 7 were migrated and attached to the transparent display electrode 4 so that the cell displayed the white color of the attached charged particles 7, and in the right cell, the positively charged white particles 7 were migrated and attached to the counter electrode 5, whereby the right cell exhibited the black color of the colored insulating liquid 6. The response speed was 50 msec. The display devices of Example 1 and Comparative Example 1 exhibited similar drive characteristics.

When the external circuit was made open with respect to the display device of Comparative Example 1, no change was observed. However, after 5 hours of standing, a noticeable change in displayed colors was observed due to partial liberation and diffusion of the colored charged particles 7 from the fixing surfaces. Then, the external circuit was closed to apply the initial voltages thereby restoring the first display state, and then the transparent display electrode 4 and the counter electrode 5 were short-

circuited, whereby almost all the colored charged particles were liberated and diffused into the liquid and the color display state was lost within several minutes.

5 Separately, when the display device of Example 1 in the color display state shown in Figure 1 was similarly brought to the circuit open state, no change was observed at all even after 50 hours of standing. Then, the transparent display electrode 4
10 and the counter electrode 5 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory characteristic was confirmed.

The display devices of Example 1 and
15 Comparative Example 1 were both subjected to application of rectangular pulse voltages of 50 msec and various amplitudes. As a result, the display device of Comparative Example 1 having no adhesive layers exhibited a switching threshold voltage of ca.
20 10 volts, whereas the display device of Example 1 exhibited an increased threshold voltage of 35 volts and remarkably improved gamma-characteristic. Further even after repetition of 100 cycles of switching by application of rectangular pulse voltages of 50 msec
25 and ± 50 volts, no change in drive characteristics was observed.

Example 2

An electrophoretic display device having a structure as shown in Figure 2 using adhesive colored charged particles 13 was prepared in the same manner as in Example 1 except for using the adhesive colored charged particles 13 instead of the colored charged particles 7, omitting the adhesive layers on the electrodes and using a colored insulating liquid 6 of isoparaffin ("Isopar", mfd. by Exxon Chemical America Co.) instead of the silicone oil.

10 The adhesive colored charged particles 13 were prepared as follows. A blend of 1.5 g of 99 %-saponified PVA (polyvinyl alcohol) and 0.06 g of 90 %-saponified PVA both having an average molecular weight of 500 was dissolved in 200 g of water under heating
15 to form a PVA solution.

 The PVA solution was mixed with 90 g of a monomer mixture of n-butyl acrylate/n-butyl methacrylate (50/50 by weight), 10 g of titanium oxide powder and 1 g of ammonium persulfate, and the mixture
20 was cooled on ice in a nitrogen atmosphere, followed by dropwise addition of 1 g of tetramethylethylenediamine under vigorous stirring and 12 hours of polymerization under the state. The reaction solution was poured into methanol, and the supernatant liquid
25 was removed by decantation. The polymerizate was further washed with methanol and water to recover adhesive white particles, which exhibited $T_g = -13.6$

004070-010700

°C as measured by a differential scanning calorimeter ("DSC 3100", mfd. by Mac Science K.K.). The white particles were tacky particles at room temperature (25 °C).

5 The thus-prepared display device having a structure as shown in Figure 2 was driven by a drive circuit (not shown). More specifically, first, the electrodes 4 of a left cell and a right cell of each device were supplied with -50 volts and +50 volts, respectively, relative to the counter electrodes 5. As a result, in the left cell, the positively charged white particles 13 were migrated and attached to the transparent display electrode 4 so that the cell displayed the white color of the attached charged
10 particles 13, and in the right cell, the positively charged white particles 13 were migrated and attached to the counter electrode 5, whereby the right cell exhibited the black color of the colored insulating layer 6.

20 When the display device of this example in the color display state shown in Figure 2 was brought to the circuit open state, no change was observed at all even after 50 hours of standing. Then, the transparent display electrode 4 and the counter
25 electrode 5 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory

00479245-01000

characteristic was confirmed.

The display device of this example was subjected to application of rectangular pulse voltages of 50 msec and various amplitudes, whereby the display device exhibited a threshold voltage of 30 volts and a good gamma-characteristic similarly as in Example 1. Further even after repetition of 100 cycles of switching by application of rectangular pulse voltages of 50 msec and ± 50 volts, no change in drive characteristics was observed.

Example 3

This example is presented for describing the applicability of the present invention to a horizontal movement-type electrophoretic display device as disclosed in JP-A 10-005727.

Figure 5 is a schematic sectional view of a display device of this example including two closed cells, each corresponding to one pixel (or display segment). Referring to Figure 5, in each cell, an entire pixel-forming surface of a display substrate 1 is provided with a white display electrode 25, on a part of which a black display electrode 24 is disposed via an insulating layer 15 covering the white display electrode 25. Further, a characteristic adhesive layer 8 of the present invention is formed on the black display electrode 24 and on a part of the insulating layer 15 above the white display electrode

25. A hollow cell surrounded by the display substrate 1, the counter substrate 2 and the partitioning walls 3 is filled with an electrophoretic layer (EL)-forming mixture comprising a transparent insulating liquid 26 and black charged particles 7 dispersed in the liquid 26. In each cell, the charged particles 7 are horizontally moved relative to the display substrate 1 and selectively collected on the black display electrode 24 or the white display electrode 24 above the display substrate to effect a display.

When the black charged particles 7 in the transparent insulating layer 26 are collected on the white display electrode 25 as shown in a right cell by voltage application, the black charged particles 7 and the black display electrode 24 are observed (displayed) to the viewer through the transparent counter substrate 2. On the other hand, when the black charged particles 7 are collected on the black display electrode 24 as shown in the left cell by applying a voltage of a different polarity, the white display electrode 25 is observed to provide a white display state. If the white display electrode 25 is formed in a larger area than the black display electrode 24, the color of the white display electrode 25 provides a dominant display state. More exactly, the color of the white display electrode 25 may be determined by the color of the insulating layer 15,

000000-000000

the white display electrode 25 per se or the display substrate 1 therebelow.

A specific display device of this example was prepared as follows. A display substrate 1 was formed of a 200 μ m-thick translucent PET film. An ITO film was formed on the display substrate 1 and patterned into stripes to form white display electrodes 25, which were then coated with a white insulating layer 15 comprising PET with titanium oxide particles dispersed therein. Then, on the insulating layer 15, a dark-colored titanium carbide film was formed and patterned by photolithography including dry etching into 50 μ m-wide stripes to form black display electrodes 24.

Then, an adhesive layer 8 was formed on the electrodes with a a n-butyl acrylate-n-butyl methacrylate copolymer. More specifically, 50 wt. parts of n-butylacrylate and 50 wt. parts of n-butyl methacrylate were dissolved in toluene to form a 10 wt. % solution, and 1 wt. % of 2,2'-azobisisobutyronitrile was added thereto as a polymerization initiator, followed by 3 hours of polymerization under heating at 70 $^{\circ}$ C. to form a polymer solution. The polymer solution was then applied by spin coating over the black display electrodes 24 and the insulating layer 25 above the white display electrodes 25 to form a ca. 500 nm-thick adhesive layer 8, which exhibited a

Tg of -15.4 °C.

The display substrate 1 was further coated with a 50 µm-thick photosensitive resist ("Su-8", mfd. by 3M Co.), followed by exposure and wet development to form partitioning walls 3 of 50 µm in height. Then, a layer of heat-bonding adhesive was applied on top of the partitioning walls 3, and the respective cells surrounded by the partitioning walls 3 were filled with a mixture of a transparent insulating liquid 26 of silicone oil and black charged particles 7 of a polystyrene-carbon mixture and 1 - 2 µm in particle size. To the silicone oil, 0.5 wt. % each of alumina and silica fine particles had been added as polar ion-adsorbers. Separately, a pattern of heat-bonding agent layer was applied on a counter substrate 2, and the counter substrate 2 was superposed on the display substrate 1 with alignment of the heat-bonding agent layer to the partitioning walls 3, followed by heat-bonding to form a display device having a structure as shown in Figure 5 providing two display segments each measuring ca. 200 µm x ca. 200 µm.

Comparative Example 2

Accomparative display device was prepared in the same manner as in Example 3 except for forming a ca. 500 nm-thick polyimide film instead of the adhesive layer 8.

(Operation)

When the external circuit was made open with respect to the display device of Comparative Example 2, no change was observed. However, after 5 hours of standing, a noticeable change in displayed colors was observed due to partial liberation and diffusion of the colored charged particles 7 from the fixing surfaces. Then, the external circuit was closed to

When the external circuit was made open with respect to the display device of Comparative Example 2, no change was observed. However, after 5 hours of standing, a noticeable change in displayed colors was observed due to partial liberation and diffusion of the colored charged particles 7 from the fixing surfaces. Then, the external circuit was closed to

apply the initial voltages thereby restoring the first display state, and then the black display electrode 24 and the white display electrode 25 were short-circuited, whereby almost all the colored charged particles were liberated and diffused into the liquid and the color display state was lost within several minutes.

Separately, when the display device of Example 3 in the color display state shown in Figure 5 was similarly brought to the circuit open state, no change was observed at all even after 50 hours of standing. Then, the black display electrode 24 and the white display electrode 25 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory characteristic was confirmed.

The display devices of Example 3 and Comparative Example 2 were both subjected to application of rectangular pulse voltages of 50 msec and various amplitudes. As a result, the display device of Comparative Example 2 having no adhesive layers exhibited a switching threshold voltage of ca. 5 volts, whereas the display device of Example 3 exhibited an increased threshold voltage of 35 volts and remarkably improved gamma-characteristic. Further even after repetition of 100 cycles of switching by application of rectangular pulse voltages of 50 msec

and ± 50 volts, no change in drive characteristics was observed.

As is understood from the above examples, according to the present invention, even in a drive system such as a simple matrix drive wherein the circuit-open state is not effectively retained, a good memory characteristic is exhibited. Further, as the surface charge on the adhesive layer is never released, a stable memory characteristic can be realized for a long period. Further, a threshold voltage corresponding to an adsorption or attachment energy on the adhesive layer is imparted whereby an electrophoretic display device having a remarkably improved gamma-characteristic is realized.

15 Example 4

Figure 9 shows an example of electrophoretic display device including two closed cells each corresponding to a display segment (or pixel) and comprising two opposing electrodes 4 and 5 each having thereon a charged layer 18. More specifically, each cell is defined by a display-side transparent substrate 1, a counter substrate 2 and a partitioning wall 3, and is filled with an electrophoretic layer (EL)-forming mixture comprising a colored insulating liquid 6 and colored charged particles 7 dispersed in the insulating liquid 6. In each cell, the display-side transparent substrate 1 is provided with a

5 The electrophoretic display device may be
produced along a process described hereinbelow. In
this specific example, the charged film 18 was formed
of a tetrafluoroethylene-hexafluoropropylene copolymer
film and converted into an electret by corona
10 discharge at an elevated temperature.

The transparent display electrode 4 may be formed of any transparent conductor material capable of patterning. In this example, a 200 nm-thick indium tin oxide (ITO) film was formed by vapor deposition and patterned into electrodes 4. The counter electrodes 5 may also be formed of such transparent conductor materials and also of metal conductor

materials. In this example, a 200 nm-thick Al film was formed by vapor deposition and patterned into electrodes 5.

The respective electrodes were subjected to 5 min of Ar etching for surface roughening to provide an improved film adhesion, and then 5 μ m-thick teflon-FEP (tetrafluoroethylene-hexafluoropropylene copolymer) transparent sheets were superposed onto the electrode-retaining surfaces of the respective substrates, 10 followed by application of a load thereon, heating to 300 °C for melt-bonding of the sheets and gradual cooling to form a 5 μ m-thick coating of the sheet over the electrodes.

Then, the teflon-FEP sheets were coated with 15 a resist left in the pattern of the segments, and the exposed portions of the sheets were removed together with the electrodes therebelow by successive etching with oxygen plasma and Ar plasma, thus leaving segment electrode patterns coated with the 5 μ m-thick teflon- 20 FEP film.

The substrates carrying the film-coated electrodes were disposed within a thermostat chamber together with a knife edge electrode attached to an XYZ-displacement drive mechanism. The knife edge 25 electrode was disposed with a gap opposite to the teflon-FEP film surface. After setting the gap at 200 μ m, the temperature within the chamber was held at 300

000000-54262460

°C and a voltage of -5 kV was applied to the knife edge electrode relative to the electrode below the teflon-FEP film to cause corona discharge between the electrodes while moving the knife edge electrode parallel to the film surface reciprocally at a constant speed to expose the entire teflon-FEP film surface uniformly to the corona discharge, followed by quenching with dry nitrogen to complete an electret-forming treatment.

10 The thus treated teflon-FEP film exhibited a good transparency and also a surface potential of ca. 35 volts below that of the respective electrodes, where the formation of charged films 18 on each of the transparent display electrodes 4 and the counter
15 electrodes 5.

Then, partitioning walls 3 were formed on the counter substrate 2. The partitioning walls 3 may suitably be formed of a polymer material through any processes, e.g., a process including a sequence of
20 application of a photosensitive resin layer, exposure and wet development; a process of bonding separately produced partitioning walls; or a process of forming partitioning walls by molding on a light transmissive counter substrate 2. In this example, a process
25 including application of photosensitive varnish, exposure and wet development was repeated in three cycles to form 50 μ m-high partitioning walls 3.

Then, an electrophoretic layer-forming mixture comprising a colored insulating liquid 6 and colored charged particles 7 was placed within the partitioning walls. The colored insulating liquid 6 may be formed by dispersing or dissolving a colorant, such as dye, in an insulating liquid, such as silicone oil, toluene, xylene or high-purity kerosene. In this example, the colored insulating liquid 6 was formed by dispersing an anthraquinone-based black dye in silicone oil, and 0.5 wt. % each of ultrafine alumina and silica particles were added thereto as polar ion adsorbents.

The colored charged particles 7 may comprise pigment particles or resin particles of e.g., polyethylene or polystyrene containing powdery pigment dispersed therein capable of being charged in the colored insulating liquid 6. The colored charged particles 7 may generally have an average particle size on the order of 0.1 - 50 μm . In this example, white particles having an average particle size of 0.5 μm and prepared by dispersing white powdery pigment (titanium oxide) in polyethylene particles were used. The white resinous particles 7 thus prepared were confirmed to be positively charged in the above-prepared colored insulating liquid 6.

Finally, the transparent substrate 1 was applied onto the partitioning walls 3 with a bonding

agent to form a display device having a structure as shown in Figure 1 having two display segments each measuring ca. 500 μ m x ca. 500 μ m.

Comparative Example 3

5 A display device was prepared in the same manner as in Example 4 except for omitting the electret-forming treatment to the teflon-FEP film on the electrodes.

(Operation)

10 The thus-prepared two display devices having similar structures as shown in Figure 5 except for the presence or absence of negative charge on the films 18 were driven by a drive circuit (not shown). More specifically, first, the electrodes 4 of a left cell
15 and a right cell of each device were supplied with -50 volts and +50 volts, respectively, relative to the counter electrodes 5. As a result, in the left cell, the positively charged white particles 7 were migrated and attached to the transparent display electrode 4 so
20 that the cell displayed the white color of the attached charged particles 7, and in the right cell, the positively charged white particles 7 were migrated and attached to the counter electrode 5, whereby the right cell exhibited the black color of the colored
25 insulating liquid 6. The response speed was 50 msec. The display devices of Example 4 and Comparative Example 3 exhibited similar drive characteristics.

000000-5426450

When the external circuit was made open with respect to the display device of Comparative Example 3, no change was observed. However, after 5 hours of standing, a noticeable change in displayed colors was observed due to partial liberation and diffusion of the colored charged particles 7 from the fixing surfaces. Then, the external circuit was closed to apply the initial voltages thereby restoring the first display state, and then the transparent display electrode 4 and the counter electrode 5 were short-circuited, whereby almost all the colored charged particles were liberated and diffused into the liquid and the color display state was lost within several minutes.

Separately, when the display device of Example 4 in the color display state shown in Figure 5 was similarly brought to the circuit open state, no change was observed at all even after 50 hours of standing. Then, the transparent display electrode 4 and the counter electrode 5 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory characteristic was confirmed.

Then, the respective cells were supplied with opposite-polarity voltages, whereby the cells exhibited respectively inverted display colors. Accordingly, it was confirmed that the adsorption by

the charged films exerted little adverse effects to the drive characteristic.

Example 5

An electrophoretic display device having a structure as shown in Figure 10 sing charged films 18 comprising an inorganic dielectric of lanthanum-added lead zirconate titanate (PLZT) was prepared in the same manner as in Example 4 except for using the charged film 18 instead of the electret films 18 of teflon-FEP in Example 4. Figure 10 shows a state of the charged films 18 wherein dipole moments in respective polarization domain in a dielectric phase are uniformly oriented toward the substrates.

The PLZT charged films 18 were prepared in the following manner. PLZT films may be formed through a sol-gel process, sputtering or a CVD (chemical vapor deposition) process. The PLZT films 18 in this example were prepared by sputtering.

Each of quartz glass-made substrates 1 and 2 carrying transparent electrodes 4 and Pt-made counter electrodes 5 was coated with a 250 nm-thick PLZT (lanthanum-added lead zirconate titanate) in a stoichiometric compositional ratio by high-frequency sputtering.

The deposited amorphous PLZT film was selectively heat-treated at 550 - 650 °C for 1 min. by illumination with light from a halogen lamp to be

perovskite-form crystal structure showing ferroelectricity. The thus-formed PLZT ferroelectric film exhibited a transmittance of ca. 70 %. The PLET film was formed into desired patterns by resist patterning and dry etching.

Then, above the PLZT film on each substrate, a parallel plate metal electrode was disposed with a gap of 200 μm , and the PLZT film under heating at 90 $^{\circ}\text{C}$ was subjected to poling by applying a voltage of -1 kV to the transparent display electrodes 4 (or Pt-counter electrodes 5) relative to the parallel plate metal electrode, thereby forming charged films 18.

By using the substrates 1 and 2 provided with the charged films of PLZT, a display device having a structure shown in Figure 10 and two display segments each measuring ca. 200 μm x ca. 200 μm was prepared thereafter in the same manner as in Example 4.

The thus-prepared display device was driven by a drive circuit (not shown). More specifically, first, the electrodes 4 of a left cell and a right cell of each device were supplied with -50 volts and +50 volts, respectively, relative to the counter electrodes 5. As a result, in the left cell, the positively charged white particles 7 initially dispersed in the black insulating liquid 6 were migrated and attached to the transparent display electrode 4 so that the cell displayed the white color

of the attached charged particles 7, and in the right cell, the positively charged white particles 7 were migrated and attached to the counter electrode 5, whereby the right cell exhibited the black color of the colored insulating liquid 6. The response speed was 50 msec.

When the display device of Example 5 in the color display state shown in Figure 10 was brought to a circuit open state, no change was observed at all even after 50 hours of standing. Then, the transparent display electrode 4 and the counter electrode 5 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory characteristic was confirmed.

Example 6

This example is presented for describing the applicability of the present invention to a horizontal movement-type electrophoretic display device as disclosed in JP-A 10-005727.

Figure 13 is a schematic sectional view of a display device of this example including two closed cells, each corresponding to one pixel (or display segment). Referring to Figure 13, in each cell, an entire pixel-forming surface of a display substrate 1 is provided with a white display electrode 25, on a part of which a black display electrode 24 is disposed

via an insulating layer 15 covering the white display electrode 25. Further, a characteristic charged film 18 of the present invention is formed on the black display electrode 24 and on a part of the insulating layer 15 above the white display electrode 25. A hollow cell surrounded by the display substrate 1, the counter substrate 2 and the partitioning walls 3 is filled with an electrophoretic layer (EL)-forming mixture comprising a transparent insulating liquid 26 and black charged particles 7 dispersed in the liquid 26. In each cell, the charged particles 7 are horizontally moved relative to the display substrate 1 and selectively collected on the black display electrode 24 or the white display electrode 24 above the display substrate to effect a display.

When the black charged particles 7 in the transparent insulating liquid 26 are collected on the white display electrode 25 as shown in the right cell by voltage application, the black charged particles 7 and the black display electrode 24 are observed (displayed) to the viewer through the transparent counter substrate 2. On the other hand, when the black charged particles 7 are collected on the black display electrode 24 as shown in the left cell by applying a voltage of a different polarity, the white display electrode 25 is to provide a white display state. If the white display electrode 25 is formed in

a larger area than the black display electrode 24, the color of the white display electrode 25 provides a dominant display state. More exactly, the color of the white display electrode 25 may be determined by the color of the insulating layer 15, the white display electrode 25 per se or the display substrate 1 therebelow.

A specific display device of this example was prepared as follows. A display substrate 1 was formed of a 200 μm -thick translucent PET film. An ITO film was formed on the display substrate 1 and patterned into stripes to form white display electrodes 25, which were then coated with a white insulating layer 15 comprising PET with titanium oxide particles dispersed therein. Then, on the insulating layer 15, a dark-colored titanium carbide film was formed and patterned by photolithography including dry etching into 50 μm -wide stripes to form black display electrodes 24.

Then, a charged film 18 was formed on the electrodes with polyvinylidene fluoride (PVDF) as a polymeric ferroelectric material. More specifically, PVDF in a pellet form was dissolved in dimethylacetamide (DMA) to form a 10 wt. % solution which was then cast over the black display electrodes 24 and the insulating layer 15 on the white display electrodes and patterned to form a 2 μm -thick PVDF

film on the electrodes.

Then, above the PVDF film on the display substrate 1, a parallel plate metal electrode was disposed with a gap of 200 μm , and the PVDF film under heating at 100 $^{\circ}\text{C}$ was subjected to poling by applying a voltage of +1 kV to the black display electrodes 24 and the white display electrodes 25 relative to the parallel plate metal electrode for ca. 15 min, followed by cooling to room temperature to form charged films 18.

The display substrate 1 was further coated with a 50 μm -thick photosensitive resist ("SU-8", mfd. by 3M Co.), followed by exposure and wet development to form partitioning walls 3 of 50 μm in height. Then, a layer of heat-bonding adhesive was applied on top of the partitioning walls 3, and the respective cells surrounded by the partitioning walls 3 were filled with a mixture of a transparent insulating layer 26 of silicone oil and black charged particles of a polystyrene-carbon mixture and 1 - 2 μm in particle size. To the silicone oil, 0.5 wt. % each of alumina and silica fine particles had been added as polar ion-adsorbers. Separately, a pattern of heat-bonding agent layer was applied on a counter substrate 2, and the counter substrate 2 was superposed on the display substrate 1 with alignment of the heat-bonding agent layer to the partitioning walls 3, followed by

004070" sheet

heat-bonding to form a display device having a structure as shown in Figure 5 and two display segments each measuring ca. 200 μm x ca. 200 μm .

Comparative Example 4

- 5 A comparative display device was prepared in the same manner as in Example 6 except for forming a ca. 2 μm -thick polyimide film without poling instead of the poled PVDF films 18.

(Operation)

- 10 The thus-prepared two display devices of Example 6 and Comparative Example 4 having similar structures as shown in Figure 10 except for the use of the poled PVDF-film 18 and the non-poled polyimide film 18 were driven by a drive circuit (not shown).
- 15 More specifically, first, the black display electrodes 24 of a left cell and a right cell of each device were supplied with -50 volts and +50 volts, respectively, relative to the white display electrodes 25 placed at a ground potential. As a result, in the left cell,
- 20 the positively charged black particles 7 were migrated and attached to the black display electrode 24 so that the cell displayed the white color of the display electrode 25, and in the right cell, the positively charged black particles 7 were migrated and attached
- 25 to the white display electrode 25, whereby the right cell exhibited the black color of the charged particles 7 and the black display electrode 24. The

response speed was 50 msec. The display devices of Example 6 and Comparative Example 4 exhibited similar drive characteristics.

When the external circuit was made open with
5 respect to the display device of Comparative Example
4, no change was observed. However, after 5 hours of
standing, a noticeable change in displayed colors was
observed due to partial liberation and diffusion of
the colored charged particles 7 from the fixing
10 surfaces. Then, the external circuit was closed to
apply the initial voltages thereby restoring the first
display state, and then the black display electrode 24
and the white display electrode 25 were short-
circuited, whereby almost all the colored charged
15 particles were liberated and diffused into the liquid
and the color display state was lost within several
minutes.

Separately, when the display device of Example 6 in the color display state shown in Figure 13 was similarly brought to the circuit open state, no change was observed at all even after 50 hours of standing. Then, the black display electrode 24 and the white display electrode 25 were short-circuited, whereby no change was observed at all even after 50 hours of standing, so that the realization of a good memory characteristic was confirmed.

As is understood from the above examples,

25

[illegible]

WHAT IS CLAIMED IS:

1. An electrophoretic display device of a cell structure, comprising: at least two electrodes, fixing surfaces each associated with one of said at least two
5 electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing
10 migration of the colored charged particles toward and collective attachment onto one of the fixing surfaces; wherein at least one of the fixing surfaces and the colored charged particles is provided with an adhesive layer allowing repetitive attachment thereto
15 and separation therefrom of the colored charged particles.

2. A display device according to Claim 1, wherein said adhesive layer comprises a polymer having
20 a glass transition temperature (T_g) of -35 °C to +35 °C and comprising at least one polymer species selected from the group consisting of poly(meth)acrylate esters, poly(meth)acrylic acid poly(meth)acrylonitrile, poly(meth)acrylamide,
25 polyvinyl esters and polyvinyl ethers.

3. A display device according to Claim 1,

004070" sheet 450

wherein said fixing surfaces are each given as a surface of one of said at least two electrodes.

4. A display device according to Claim 1,
5 wherein said insulating liquid has a volumetric
resistivity of at least 10^{12} ohm.cm.

5. A display device according to Claim 1,
wherein said two electrodes are oppositely disposed
10 in the cell structure so as to allow vertical movement
of the colored charged particles between the
electrodes.

5. A display device according to Claim 1,
15 wherein said two electrodes are disposed on an
identical plane in the cell structure so as to allow
horizontal movement parallel to the plane of the
colored charged particles.

20 7. An electrophoretic display device of a cell structure, comprising: at least two electrodes, fixing surfaces each associated with one of said at least two electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored
25 charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing

migration of the colored charged particles toward and collective attachment onto one of the fixing surfaces; wherein the fixing surfaces are provided with a charged film having a constant surface charge of a polarity opposite to that of the colored charged particles.

8. A display device according to Claim 7, wherein said charged film is formed on the fixing surfaces given by the electrodes.

9. A display device according to Claim 7, wherein said charged film comprises a ferroelectric material or an electret material.

10. A display device according to Claim 7, wherein said insulating liquid has a volumetric resistivity of at least 10^{12} ohm.cm.

11. A display device according to Claim 7, wherein said two electrodes are oppositely disposed in the cell structure so as to allow vertical movement of the colored charged particles between the electrodes.

12. A display device according to Claim 7, wherein said two electrodes are disposed on an

5

15

20

25

ABSTRACT OF THE DISCLOSURE

An electrophoretic display device capable of realizing a stable memory characteristic without relying on a circuit-open state is provided. The
5 electrophoretic display device has a cell structure including at least two electrodes, fixing surfaces each associated with one of said at least two electrodes, an electrophoretic layer disposed in the cell and comprising an insulating liquid and colored
10 charged particles disposed in the electrophoretic layer, and voltage application means for applying a voltage between the electrodes thereby causing migration of the colored charged particles toward and collective attachment onto one of the fixing surfaces;
15 wherein at least one of the fixing surfaces and the colored charged particles is provided with an adhesive layer allowing repetitive attachment thereto and separation therefrom of the colored charged particles; or the fixing surfaces are provided with a charged
20 film having a constant surface charge of a polarity opposite to that of the colored charged particles.






FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG. 6




FIG. 7

Diagram of a device 10. The left part is a cross-sectional view showing layers 1, 4, 7, 6, 5, and 2. A central region contains a pattern of dots. The right part is a circuit diagram showing a switch and two battery symbols connected in parallel.

Diagram of a plasma display cell 10. The cell contains a gas mixture 6, a first electrode 4, and a second electrode 5. The cell is connected to a power source 10, which includes a transformer 7 and a capacitor 8.

FIG. 8C




FIG. 9




FIG. 10

002070" 5425/460




FIG. IIA




FIG. IIB




FIG. IIC




FIG. 12




FIG. 13




FIG. 14

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
(Page 1)**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled ELECTROPHORETIC
DISPLAY DEVICE

the specification of which ☒ is attached hereto ☐ was filed on _____ as United States Application
No. or PCT International Application No. _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filed (Day/Mo./Yr.)	(Yes/No) Priority Claimed
JAPAN	11-003186	08/JANUARY/1999	Yes
JAPAN	11-003187	08/JANUARY/1999	Yes
JAPAN	11-301180	22/OCTOBER/1999	Yes
JAPAN	11-301179	22/OCTOBER/1999	Yes

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Application No.	Filed (Day/Mo./Yr.)	Status (Patented, Pending, Abandoned)
-----------------	---------------------	---------------------------------------

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor ETSURO KISHI

Inventor's signature _____

Date _____ Citizen/Subject of Japan

Residence 2340-1 Shindo, Sagamihara-shi, Kanagawa-ken, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko

3-chome, Ohta-ku, Tokyo, Japan

(Page 2)

Second Inventor's signature _____

Citizen/Subject of Japan

Residence 5-5-3 Morinosato, Atsugi-shi, Kanagawa-ken, Japan

Post Office Address C/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko

3-chome, Ohta-ku, Tokyo, Japan

TTCG\lmj